

VERTI CLAD

780.451.5482
www.lenmak.com
Toll Free 888.451.5482

VertiClad Soffit System

VertiClad Panel Systems by Lenmak Exterior Innovations Inc. offer a sleek, low-cost alternative with concealed-fasteners. Three panel widths, available recessed reveal, & stiffening rib options create visual interest. A wide range of prefinished steel colours & in-house cut-to-length coil processing ensure a perfect fit for every project.

Advantages

Design

- Cut-to-length & slaying capability offers flexibility in panel lengths to suit many applications
- Available reveal & stiffening rib features allow customization at no additional cost
- Easily integrates with surrounding exterior products & fully adaptable to existing wall conditions

Colour

- Available in 22ga prefinished steel & galvalume
- 13 standard (SMP) colours & 12 premium (PVDF) colours
- Industry-leading high-durability finishes meet or exceed architectural standards for interior & exterior applications
- All colours offer matching prefinished steel trim in pre-programmed profiles for one-stop ordering, or available custom trim details to suit special circumstances

Time

- Lean manufacturing & in-house master coil processing reduces lead time & minimum order size
- Proprietary robotic inventory management allows flexibility to add small quantities from sheeted inventory
- Online ordering system shortens processing time for quotes & orders, preventing costly errors & lost time on-site

Price

- Available in standard & premium finishes to ensure best value for each specific project
- Produced to exact lengths to minimize on-site modification & waste created during installation

Sustainability

- Panels contain a minimum of 30% recycled content; 24% post-consumer and 6.8% post-industrial (possibility for LEED credits 4.1 or 4.2)
- Local manufacturing and sustainable practices reduce carbon footprint





VertiClad Panel System with V-Rib

Keep it on the straight & narrow.

VertiClad panels are suitable for vertical & horizontal cladding as well as soffit applications.

- 6", 8", or 12" coverage available
- 1" panel thickness
- ¼", ½", 1" or no reveal between panel planks
- Available stiffening rib in centre of panel for longer-length applications

VertiClad Vertical or Horizontal Cladding

- Recommended installation over steel girt or Thermal Max clip
- Male/Female interlocking edges conceal fasteners for a sleek contemporary look
- Available up to 21' long* for a visually seamless installation
- Colour-matched flashing components maintain building envelope & drainage requirements with style
- Designed to optimize value vs cost without loss of aesthetic appeal

VertiClad Panel as Soffit

- Ideal for commercial applications
- Available 1¼" venting strip accommodates air-flow requirements even on projects with complex roof systems
- Fasteners are entirely concealed by adjacent panels & surrounding materials
- Can be run parallel or perpendicular to wall to suit aesthetic requirements of every job

Panel Type	Material	Standard Width	Standard Depth	Standard Reveal Size	Length	Orientation
VertiClad Wall Panel	22ga steel, SMP, PVDF finishes or Galvalume	6" including reveal 8" including reveal 12" including reveal	1"	0.25" 0.5" 1" No Reveal*	36" (3') Min. 252" (21') Max.*	Vertical or Horizontal
VertiClad Soffit Panel	22ga steel, SMP, PVDF finishes or Galvalume	6" including reveal 8" including reveal 12" including reveal	1"	0.25" 0.5" 1" No Reveal*	36" (3') Min. 252" (21') Max.* or 192" (16') Max for Vented	Parallel or Perpendicular to Walls

*Extremely long panels may require stiffening ribs and/or reveals between panels to accommodate expansion/contraction & maintain system & aesthetic performance. Consult Lenmak's Project & Design team for application-specific limitations on panel length & appropriate trim/accessory details.